

TRITON 9

MULTI-PURPOSE SUPPORT VESSEL



Class	CR100 _主 , CSM _主 , Work Boat, Coastal Service
Flag	Republic of China
P.O.R	Kaohsiung
Year Built	2008
Builder	Nam Cheong Dockyard S/B
IMO	9466075

DIMENSION

L.O.A.	34.00 m
Beam	8.00 m
Depth	3.30 m
Draft (max)	2.337 m
GRT	217
NRT	65

CARGO CAPACITIES

Deck Cargo	10 Tonnes
Deck Loading	3.0 Tonnes/m ²
Deck Area	84 m ²
Fresh Water	43.7 m ³
Ballast Water	15.16 m ³
Fuel Oil	60.3 m ³
Dispersant	7.18 m ³
Foam	1.40 m ³

ACCOMMODATION

1 Man cabin	2x 1 (2)
3 Men Cabin	2x 3 (6)
4 Men cabin	1x 4 (4)
Total	12 berths

PERFORMANCE

Speed	10 knots
--------------	----------

SAFETY EQUIPMENT

Rescue Boat	1x 6 men Rescue Boat
--------------------	----------------------

PROPULSION & POWER PLANT

Propellers	2x 537KW Fixed Pitch Propellers
Bow Thruster	1x 1.0T Thrust each
Main Engine	2x 537KW @ 1800 rpm
Main Generator	2x 80KW, 415V/3Ph/50Hz

DECK MACHINERY

Tow Hook	1X5 Tonnes SWL
Capstan	1X3 Tonnes SWL
A-Frame	1x5 Tonnes SWL @ 2900mm Outreach

CARGO HANDLING CAPACITY

Fresh Water	1x 13 m ³ /hr @ 20 m head
Ballast Water	1x 30 m ³ /hr @ 30 m head
Fuel Oil	1x 13 m ³ /hr @ 20 m head

NAVIGATION EQUIPMENT

Radar, Magnetic Compass, Satellite Compasses, GPS, AIS Echo Sounder, Speed Log, Navtex, BNWAS

COMMUNICATION EQUIPMENT


GMDSS A1+A2, VHF Radios, Intercom System, EPIRB Public Address, SART

FIRE-FIGHTING EQUIPMENT

External FiFi	Pump: 1x 1200 m ³ /hr @ 130 MLC
(Half-FiFi)	Monitor: 2x 600 m ³ /hr (water)
External FiFi	Pump: 1x 50 m ³ /hr @ 100 MLC
(Secondary)	Monitor: 1x 50 m ³ /hr (water/foam)
Oil Dispersant	2x 6m spray booms with nozzles



TRITON 9 | MULTI-PURPOSE SUPPORT VESSEL



THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE SUPPLIED ON THE UNDERSTANDING THAT THEY ARE THE EXCLUSIVE PROPERTY OF WYNNERGY MARINE CO., LTD. THEY MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT PERMISSION IN WRITING.